DATASHEET

TRIMBLE 5700 GPS RECEIVER

KEY FEATURES

Proven technology provides dependable performance and precision

Flexible configurations put you in total control

Rugged, high-performance hardware is built to last

Compatible with Trimble Integrated Surveying® technology



ONE RECEIVER, MANY CONFIGURATIONS, FOR GREATER FLEXIBILITY AND CHOICE The Trimble® 5700 GPS receiver is an advanced, but easy-to-use, surveying instrument that is rugged and versatile enough for any job.

Combine your 5700 with the antenna and radio that best suit your needs, and then add the Trimble controller and software of your choice for a total surveying solution. The powerful 5700 GPS system will provide all the advanced technological power and unparalleled flexibility you need to increase your efficiency and productivity in any surveying environment.

ADVANCED GPS RECEIVER TECHNOLOGY

The 5700 is a 24-channel dual-frequency RTK GPS receiver featuring the advanced Trimble Maxwell[™] technology for superior tracking of GPS satellites, increased measuring speed, longer battery life through less power use, and optimal precision in tough environments. WAAS and EGNOS capability lets you perform real-time differential surveys to GIS grade without a base station.

MODULAR DESIGN FOR VERSATILITY

For topographic, boundary, or engineering surveying, clip the receiver to your belt, carry it in a comfortable backpack, or configure it with all components on a lightweight range pole. With the receiver attached to your site vehicle, you can survey a surface as fast as you can drive! For control applications, attach the receiver to a tripod ... it's designed to work the way your job requires.

FULL METAL JACKET ... AND LIGHTWEIGHT

The 5700 GPS receiver boasts the toughest mechanical and waterproofing specs in the business. Its magnesium alloy case is stronger than aluminum, but also 30% lighter—the 5700 weighs just 1.4 kg (3 lb) with batteries. Whether you're collecting control points on a tripod, or scrambling down a scree slope collecting real-time kinematic data, the receiver is light enough and tough enough to carry on performing.

FAST AND EFFICIENT DATA STORAGE AND COMMUNICATIONS

Use the receiver's CompactFlash memory to store more than 8,900 hours of continuous L1/ L2 data collection at an average of 15-second intervals. Transfer data to a PC at speeds of more than 1 megabit per second through the super-fast USB port. With the option of a UHF radio modem built in, the 5700 can provide RTK communications without the need for cables or extra power!

EXPERIENCE TRIMBLE INTEGRATED SURVEYING[™]

The Trimble 5700 GPS receiver is designed to support Trimble's original Integrated Surveying[™] solution. Combine your GPS and optical data in one job file in powerful Trimble field software such as Trimble Survey Controller[™], then transfer the job file seamlessly to your Trimble office software, such as Trimble[®] Business Center, for processing.

Whenever you're facing a new surveying challenge, your partnership with Trimble places the right tools and techniques, including GNSS technology, at your fingertips. Each Trimble system seamlessly integrates via shared workflows and technologies, making your everyday job site a place where the whole is greater than the sum of its parts: Welcome to the Trimble Connected Site.



PERFORMANCE SPECIFICATIONS

Measurements

- Trimble R-Track technology
- Advanced Trimble Maxwell[™] Custom Survey GNSS Chip
- High precision multiple correlator for GNSS pseudorange measurements · Unfiltered, unsmoothed pseudorange measurements data for low noise,
- low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Signal-to-Noise ratios reported in dB-Hz
- Proven Trimble low elevation tracking technology
- 24 Channels L1 C/A Code, L1/L2 Full Cycle Carrier
- 2 additional channels for SBAS WAAS/EGNOS support

Code differential GPS positioning¹

Horizontal	
Vertical	
WAAS differential positioning accuracy ² typically <5 m 3DRMS	

Static and FastStatic GPS surveying¹

Horizontal	±5 mm + 0.5 ppm RMS
Vertical	±5 mm + 1 ppm RMS

Kinematic surveying¹

Horizontal ±10 mm + 1 ppm RMS
Vertical
Initialization time ³ typically <10 seconds
Initialization reliability ⁴ typically >99.9%

HARDWARE

Physical

Casing	. Tough, lightweight, fully sealed magnesium alloy
	(5.3 in x 3.4 in x 9.5 in)
Weight	1.5 kg (3 lb) with internal batteries, internal radio,
	internal battery charger, standard UHF antenna.
Less that	an 4 kg (8.8 lb) entire RTK rover including batteries
_	for 7 hours, range pole, controller and bracket
Temperature ⁵	
Operating	40 °C to +65 °C (–40 °F to +149 °F)
Storage	40 °C to +80 °C (–40 °F to +176 °F)
Humidity	100%, condensing
Water/dustproof	IP67 dustproof, protected from temporary
	immersion to depth of 1 m (3.28 ft)
Shock and vibration	Tested and meets the following
	environmental standards:
Shock Nor	n-operating: Designed to survive a 1 m (3.3 ft) drop
on	to concrete. Operating: to 40 G, 10 msec, sawtooth
Vibration	MIL-STD-810F, FIG.514.5C-1

Electrical

- Power input 10.5 V DC to 28 V DC with over-voltage protection
- Two rechargeable, removable 7.4 V, 2.4 Ah Lithium-Ion batteries in internal battery compartments
- Power consumption:
 - 4.0 W for receiver only (tracking and logging)
 - 4.4 W including internal radio (not receiving CMR)
- 5.9 W (tracking SV's, logging at 1 Hz, external antenna and RTK in Fixed mode)
- Operating times on internal battery:
- >10 hours postprocessed
- 6-8 hours RTK (with two 2.4 Ah batteries)
- · Battery charger internal with external AC power adapter; no requirement for external charger
- Power output:
 - 6.5 V to 20 V (Port 1) Max 50 mA
 - 10.5 V to 28 V (Port 3) max 0.5 A
- Certification: FCC Part 15B Class B, ICES-003 Class B, CE Mark, and C-tick; FCC and Industry Canada Radio Approval; IEC 60950-1 Safety

Communications and Data Storage

- 2 external power ports, 2 internal battery ports, 3 serial ports
- Integrated USB for data download speeds in excess of 1 megabit per second
- Fully integrated, fully sealed internal UHF radio modem option
- External cell phone support for GSM/GPRS/CDPD modems for RTK and **VRS** operations
- CMR+, RTCM 2.1, RTCM 2.3, RTCM 3.0, RTCM 3.1 Input and Output
- 16 NMEA outputs. GSOF and RT17 output
- Dual event marker inputs
- 1 Pulse Per Second Output
- Data Storage on 256 MB CompactFlash memory at 15 second intervals:
 - 8900 hours of raw observables, with 8 SV average

- Accuracy and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended survey practices. 2 Depends on WAAS/EGNOS system performance.
- 3 May be affected by atmospheric conditions, signal multipath, obstructions and satellite geo 4 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
- 5 Receiver will operate normally to -40 °C, and internal batteries are rated to -20 °C.

Specifications subject to change without notice

© 2007-2008, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Integrated Surveying, Maxwell, and Trimble Survey Controller are trademarks of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022543-074E (08/08)

NORTH AMERICA

Trimble Engineering & Construction Group 5475 Kellenburger Road Dayton, Ohio 45424-1099 • USA 800-538-7800 (Toll Free) +1-937-245-5154 Phone +1-937-233-9441 Fax

FUROPE Trimble GmbH

Am Prime Parc 11 65479 Raunheim • GERMANY +49-6142-2100-0 Phone +49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Navigation Singapore Pty Limited 80 Marine Parade Road #22-06, Parkway Parade Singapore 449269 • SINGAPORE +65-6348-2212 Phone +65-6348-2232 Fax

((C



TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

www.trimble.com